## MOBILE COLUMN LIFT

## HYDROLIFT WITH AGRICULTURAL ADAPTERS, WIRELESS, BATTERY POWERED

Hydrolift's mobile wheel gripper system AGRAR with its adapters is universally applicable and thus excellent for the safe lifting of tractors of various manufacturers. In combination with selectable support pieces, it is a comfortable workshop assistant.

+ Double load protection ensures safety + Intuitive operation + Quick change of position by forklift possible The modular design allows the additional expansion from 2 to 4, 6 The large-volume production in our or 8 lifting units. ISO-certified production facilities allows a consistently high manufacturing quality. Double load protection due to continuously adjustable hydraulic safety device (shut-off valve) and self-lo-Symbols that are2 easy to undercking mechanical safety catch. stand and well-arranged push-buttons facilitate operation. Software The communication of the indiviupdates are made via SD card. dual lifting units is wireless based on the IEEE 802.15.4 standard. Emergency stop buttons present on each column. The integrated charger allows charging while using the HYDRO-Easy Drive: Low-friction rollers, LIFT. One hour of fast charging allows another complete lifting/ literally speaking, make setting up the workplace a piece of cake. lowering operation. Hydro Protect: For protection against external influences, the lifting cylinder is located in the lifting carriage. The motor and the hydraulic unit are The synchronization control ensures absoalso completely covered. lute synchronization of all lifting units,

No master column - all functions are available on each wheel gripper column.

even with unequal load distribution.

## HIGHLIGHTS IN DETAIL



1 Rear support adapter with additional locking bars


2 Front support adapter with various support adapters

Movable drawbar with self-deflecting steering chassis, double roller and integrated parking brake prevents unintentional rolling away of the lifting unit

4 Forklift adapters allow quick and easy transport of the wheel grippers in the workshop

Suitable for tractors with a wheel base of at least 1.100 mm
The well-arranged control elements characterize the operator friendliness of the wheel gripper system







	Model HYDRO-LIFT	S3 6,2	S3 7,5	S2 8,2
	Capacity	6,2 t	7,5 t	8,2 t
	Lifting time	65 sec.	65 sec.	78 sec.
	Lowering time	54 sec.	54 sec.	54 sec.
	Lift cycles fully loaded	14	14	14
	Driving power	3 kW	3 kW	3 kW
A	Stroke	1753 mm	1753 mm	1759 mm
B	Width	1107 mm	1107 mm	1156 mm
C	Height	2260 mm	2260 mm	2590 mm
	Weight per column	630 kg	630 kg	730 kg

## ACCESSORIES







 LED lighting kit 2 standard
SmartCart Agrar - Trolley for the tractor adaptor
Protective cover - Jet water protection for hydro lift wheel gripper column

