


TYRE CHANGERS
Automatic with tilt tower




 **Ravaglioli**



**SERIE
SG45.26**

TYRE CHANGERS

Automatic with tilt tower



Storage area on selected models.

Tool head featuring **pneumatic positioning** with up and down movement. (DP models only)

Professional **pneumatic auxiliary arm** for selected models.

Plate with diameter up to 26" with **adjustable jaws**.

SG 45.26DPW Plus

All pedals are easy to reach without the need for unnatural movements.

Pneumatic bead breaker with **adjustable shovel**. (DPW Plus model only).



TYRE CHANGERS

Automatic with tilt tower

The **frame** and **tilt tower** are extremely strong so all types of car and van wheels can be changed while ensuring **utmost safety** for the tyre and rim.



Ø 40 mm
tool rod



60 x 60 mm
horizontal arm



The optimised design provides easy access to internal components and simple adjustments.





Motor with inverter.
Allows the operator to change the wheel rotation speed (0 - 15 rpm).
When stress on the bead increases, rotation automatically slows down to prevent damage to the tyre.

CONFIGURATIONS	SG 45.26D	SG 45.26DP	SG 45.26D Plus	SG 45.26DW Plus	SG 45.26DPW Plus
Plastic tool				✓	✓
Pneumatic tool positioning		✓			✓
Adjustable bead breaker shovel					✓
Pneumatic bead press arm			✓	✓	✓
Tool & accessories storage				✓	✓
WDK certificate				✓	✓

Technical data


	SG45.26DPW Plus	SG45.26DW Plus	SG45.26D Plus	SG45.26DP	SG45.26D
	RAV. SG45X.202048	RAV. SG45X.202178	RAV. SG45X.202161	RAV. SG45X.202185	RAV. SG45X.202192
Max. torque (Nm)	1200 (885 ft.lbs)	1200 (885 ft.lbs)	1200 (885 ft.lbs)	1200 (885 ft.lbs)	1200 (885 ft.lbs)
Outer clamping range	10" - 26"	10" - 26"	10" - 26"	10" - 26"	10" - 26"
Inner clamping range	13" - 28.5"	13" - 28.5"	13" - 28.5"	13" - 28.5"	13" - 28.5"
Max. wheel diameter	45"	45"	45"	45"	45"
Max. rim width	16"	16"	16"	13.5"	13.5"
Max. wheel width	16"	16"	16"	16"	16"
Bead breaker force	11900 N (2675 lbf)	11900 N (2675 lbf)	11900 N (2675 lbf)	11900 N (2675 lbf)	11900 N (2675 lbf)
Air supply	8 - 10 bar (116 - 145 psi)	8 - 10 bar (116 - 145 psi)	8 - 10 bar (116 - 145 psi)	8 - 10 bar (116 - 145 psi)	8 - 10 bar (116 - 145 psi)
Power inverter motor	0.75 kW (1 Hp)	0.75 kW (1 Hp)	0.75 (1 Hp)	0.75 kW (1 Hp)	0.75 kW (1 Hp)
Power supply	200 - 240 V 50 - 60 Hz	200 - 240 V 50 - 60 Hz	200 - 240 V 50 - 60 Hz	200 - 240 V 50 - 60 Hz	200 - 240 V 50 - 60 Hz
Phases	1 Ph	1 Ph	1 Ph	1 Ph	1 Ph
Typical current draw (A)	10	10	10	10	10
Rotation speed	0 - 16 rpm	0 - 16 rpm	0 - 16 rpm	0 - 16 rpm	0 - 16 rpm



Accessories



G800A11
Plastic guard for side
bead breaker shovel
(1 pc.)



G800A117
Plastic quick insertion
guard for tool head
(1 set, 2 pcs.)



VSG.8A137.902160
Tubeless inflation kit
for plate tyre changers



VSG.8A138.902184
Front wheel lift



VSG.8A139.902207
Bead breaker roller
kit with bead pusher
arm | PL100 equipment
necessary



VSG.8A140.902221
Plastic guard for jaws
(1 set, 4 pcs.)



VSG.8A140.902245
Plastic guard for jaws
(10 set, 40 pcs.)



VSG.8A141.902269
Side column storage
with built-in gauge



VSG.PL100.900401
Bead pusher device
for tyre changers with
tilting pole (installation
on right side)

RAV Italy

Vehicle Service Group Italy S.r.l.

Via Filippo Brunelleschi 9
44020 Ostellato (FE)
Italy

+39.051.6781511
+39.051.846349
rav@ravaglioli.com

RAV France

RAV France SARL

4, Rue De Longue Raie
ZAC de la Tremblaille
91220 Le Plessis Pâté
France

+33.1.60.86.88.16
+33.1.60.86.82.04
Info.fr@ravaglioli.com

RAV Germany

BlitzRotary GmbH

Hüfingerring Straße 55
78199 Bräunlingen
Germany

+49.771.9233.0
+49.771.9233.99
ravd@ravaglioli.com

RAV UK

Vehicle Service Group UK Ltd

3 Fourth Avenue,
Bluebridge Industrial Estate
Halstead, Essex, CO9 2SY
United Kingdom

+44.1787.477711
+44.1787.477720
rav@ravaglioli.com