



| KPH35EVP-SPOA35EVP - specifications | |
|-------------------------------------|---------------------|
| Number of columns | 2 |
| Lifting Capacity | 3500 kg |
| Required ceiling height | 4250 mm (*) |
| Height overall | 4170 mm (*) |
| Outside columns | 3162 mm (*) |
| Inside columns | 2700 mm (*) |
| Drive-Thru | 2456 mm (*) |
| Front Arm Min | 668 mm |
| Front Arm Max | 1143 mm |
| Rear Arm Min | 686 mm |
| Rear Arm Max | 1474 mm |
| Max. pad Height | 170 mm |
| Min. pad Height (short arm) | 114 mm |
| Lifting height max. | 2020 mm |
| Rise | 1850 mm |
| Lifting time | 32 secs |
| Lowering time | 30s [**] |
| Power supply | 400 V 50 Hz 3Ph |
| Driving power | 2.6 Kw |

* configurable

| | | | | |
|--------------------|-------------|----------------|-----------|------|
| DATA | DIS | NOTE | | |
| 04/11/2024 | L. Pontillo | SOSTITUISCE: * | | |
| DESCRIZIONE | | | CODICE | I.A. |
| KPH35EVP-SPOA35EVP | | | 049807030 | 01 |

F
E
D
C
B
A