



KPH45S - SPOA45S - specifications

| | |
|-------------------------|---------------------|
| Number of columns | 2 |
| Lifting Capacity | 4500 kg |
| Required ceiling height | 4250 mm (*) |
| Height overall | 4170 mm (*) |
| Outside columns | 3244 mm (*) |
| Inside columns | 2900 mm (*) |
| Drive-Thru | 2594 mm |
| Front Arm Min | 550 mm |
| Front Arm Max | 1106 mm |
| Rear Arm Min | 876 mm |
| Rear Arm Max | 1472 mm |
| Max. pad Height | 155 mm |
| Min. pad Height | 95 mm |
| Lifting height max. | 2005 mm |
| Rise | 1850 mm |
| Lifting time | 37 secs |
| Lowering time | 34s [*] |
| Power supply | 400 V 50 Hz 3Ph |
| Driving power | 3.5 Kw |

* configurable

| | | |
|--|--------------------|----------------------------|
| DATA 27/11/2024 | DIS L. Pontillo | NOTE SOSTITUISCE: * |
| DESCRIZIONE KPH45S - SPOA45S | | CODICE 049807020 |
| 8 | 7 | 6 |
| 4 | 3 | 2 |
| FORM A3 | | 1 |

F
E
D
C
B
A

F
E
D
C
B
A

| | | | | |
|------------------|-------------|----------------|-----------|------|
| DATA | DIS | NOTE | | |
| 27/11/2024 | L. Pontillo | SOSTITUISCE: * | | |
| DESCRIZIONE | | | CODICE | I.A. |
| KPH45S - SPOA45S | | | 049807020 | 00 |

STAMPATO IL

+

|

+

8

7

6

5

4

FORM A3

3

2

1